

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
6 September 2002 (06.09.2002)

PCT

(10) International Publication Number  
**WO 02/069252 A2**

(51) International Patent Classification<sup>7</sup>: **G06M 1/00**

27514 (US). **BRACE, Geoff** [GB/US]; 3421 Savan Court, Raleigh, NC 27613 (US).

(21) International Application Number: PCT/GB02/00767

(22) International Filing Date: 22 February 2002 (22.02.2002)

(74) Agents: **ALEXANDER, Thomas, Bruce** et al.; Boulton Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0104556.6 23 February 2001 (23.02.2001) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **OUYANG, Tian-hong** [US/US]; 161 Kingston Drive, Chapel Hill, NC

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: DOSAGE COUNTING DEVICES



(57) Abstract: Apparatus comprising a housing (1) defining a portion (2) for receiving in use a dose-dispensing container (20), the housing containing a dose counter comprising an annular counter member (40) and a driving member (41), the driving member comprising a planar ring portion (50) and first and second sets of flexible teeth (51, 52) depending from opposite sides of the planar ring portion, the first set of dependant flexible teeth (51) engaging a first series of teeth (47) formed on the annular counter member, wherein on movement of the received dose-dispensing container towards the driving member the first and second sets of dependant flexible teeth are caused to flex towards the plane of the ring portion to thereby incrementally rotate the annular counter member in a first direction relative to the housing.

WO 02/069252 A2



European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished upon receipt of that report*

- 1 -

DOSAGE COUNTING DEVICES

The present invention relates to counting devices for use with dose-dispensing delivery apparatus which require an axial force for operation.

It has been recognised that there is a need to provide accurate information to the user of a dose-dispensing delivery apparatus concerning the number of doses delivered from, or remaining in, the apparatus. Without such accurate information there is the danger that a user will forget how many doses have been delivered and hence take a greater or fewer number of doses than is required. There is also the danger that a user may be unaware that the delivery apparatus is empty or close to empty. Hence, in an emergency situation, the user may seek to take a dose from the delivery apparatus only to find that there are no doses left in the apparatus. This is especially dangerous where the delivery apparatus is for use in dispensing medicinal compounds for the treatment of chronic or acute symptoms, for example, as in the case of a pressurised metered dose inhaler used for treating asthmatic reactions.

A number of devices have been proposed to count the number of doses delivered or remaining in a delivery apparatus. WO95/08484 teaches a dose counting device for use with an aerosol medication dispenser. The device works by translating a non-rotative force on an outer cover into a rotation of an indicator wheel by use of a set of flexible pawls engaged with a set of teeth. The pawls depress and thereby extend circumferentially when the applied force forces them to effect a rotation of the teeth. This device has, however, been found to have disadvantages. The reliability of operation of the counting device depends on the relationship between the stiffness of the internal spring bias of the

- 2 -

medication dispenser and the pawls. If the pawls are too stiff relative to the internal spring bias then the medication dispenser may dispense a dose before the pawls flex sufficiently to rotate the indicator wheel; a dose would be delivered without the counter registering it. Alternatively, if the pawls are too flexible relative to the internal spring bias then the pawls may flex sufficiently to rotate the indicator wheel before the medication dispenser has dispensed a dose; a dose would be registered by the counter but not actually delivered.

The present invention seeks to provide a dosage counting device which overcomes these problems.

Accordingly, the present invention provides apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising an annular counter member and a driving member, the driving member comprising a planar ring portion and first and second sets of flexible teeth depending from opposite sides of the planar ring portion, the first set of dependant flexible teeth engaging a first series of teeth formed on the annular counter member, wherein on movement of the received dose-dispensing container towards the driving member the first and second sets of dependant flexible teeth are caused to flex towards the plane of the ring portion to thereby incrementally rotate the annular counter member in a first direction relative to the housing.

The present invention also provides apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising an annular counter member, a driving member for translating reciprocal motion of the received dose-dispensing container into rotary motion of the annular counter member, and a support member for supporting the

- 3 -

annular counter member and driving member in proper alignment with the received dose-dispensing container, wherein the support is an interference fit in the housing such that a first actuation of the received  
5 dose-dispensing container sets the position of the support relative to the received dose-dispensing container and housing.

An embodiment of the present invention will now be described, by way of example only, with reference  
10 to the accompanying drawings, in which:

Figure 1 is a cross-sectional view of a dispensing apparatus according to the present invention; and

15 Figure 2 is an exploded perspective view of part of the dispensing apparatus of Figure 1.

In the following description, the invention will be illustrated, by way of example only, with respect  
20 to a pressurised dispensing container capable of delivering successive doses of a product in an aerosol form.

Figures 1 and 2 illustrate a dispensing apparatus comprising a housing 1 having a cylindrical portion 2 with upper and lower ends. The upper end 6 is open  
25 whilst the lower end is closed off by a basal wall portion 7. A mouthpiece 3 which communicates with the cylindrical portion 2, depends laterally from the lower end of the cylindrical portion 2. The mouthpiece 3 defines an outlet duct 4 which terminates  
30 in an outlet 5 of the mouthpiece 3.

An inwardly directed valve stem receiving block 9 is integrally formed with the basal wall portion 7 and has its longitudinal axis aligned co-axially with a  
35 longitudinal axis of the cylindrical portion 2 of the housing 1. The valve stem receiving block 9 defines a receiving bore 12 which is open to the cylindrical

- 4 -

portion 2 and an orifice 10 which is open to the outlet duct 4 of the mouthpiece 3. The receiving bore 12 and orifice 10 are linked by a duct 11.

Eight circumferentially spaced inwardly directed longitudinal ribs 14 are provided on the internal wall of the cylindrical portion 2.

In use a pressurised dispensing container 20 is received in the cylindrical portion 2. The pressurised dispensing container 2 comprises a canister body 21 defining a storage chamber for housing the product to be dispensed. The canister body 21 is closed off at one end by a metering valve (not shown) having a valve stem 22 which extends externally from the metering valve. The metering valve is retained in the canister body by a crimped ferrule 23.

When the pressurised dispensing container 20 is inserted into the housing 1, the valve stem 22 is received in receiving bore 12 of the valve stem receiving block 9. An annular air gap 13 exists between the internal wall of the cylindrical portion 2 and the canister body 21 to allow air to flow through the dispensing apparatus in use.

According to the present invention, a dosage counter is provided in housing 1. The counter comprises an indicator wheel 40, toothed wheel 41, bearing plate 42 and support ring 70. Each of the indicator wheel 40, toothed wheel 41, bearing plate 42 and support ring 70 are generally annular in form. The indicator wheel 40 comprises a peripheral wall 43 on which are marked indicia 45 in the form of numerals. An annular flange portion 44 depends from an upper edge of the peripheral wall 43 and defines a central aperture 48. The upper surface of annular flange portion 44 is formed into a series of teeth which will be denoted as the upper teeth 47 of the indicator wheel 40. The lower edge of the peripheral

- 5 -

wall 43 is formed into a series of teeth which will be denoted as the lower teeth 46 of the indicator wheel 40.

5 The toothed wheel 41 comprises a generally planar annular disc 50 formed from an elastic material such as sheet metal. A series of circumferentially spaced teeth are formed in the annular disc 50. Alternate teeth are directed upwardly and downwardly to depend out of the plane of the disc 50 to form upwardly  
10 directed teeth 52 and downwardly directed teeth 51. A central aperture 53 is defined at a centre of the annular disc 50.

The bearing plate 42 also comprises an annular disc 55 defining a central aperture 56. A lower face  
15 of the annular disc 55 is formed into a series of teeth which will be denoted as the lower teeth 57 of the bearing plate 42. A series of eight circumferentially spaced notches 58 are formed in the periphery of the bearing plate 42.

20 The support ring 70 comprises an annular disc 71 whose upper face 72 is formed into a series of teeth which will be denoted as the upper teeth 73 of the support ring. The annular disc 71 defines a central aperture 74.

25 The indicator wheel 40, toothed wheel 41, bearing plate 42 and support ring 70 are assembled in the housing 1 as follows:

The support ring 70 is positioned lowermost. Above the support ring 70 is positioned the indicator  
30 wheel 40. Above the indicator wheel 40 is positioned the toothed wheel 41. Above the toothed wheel 41 is positioned the bearing plate 42.

The support ring 70 forms a push-fit with the internal wall of the cylindrical portion 2 of the  
35 housing 1. The support ring 70 is pushed down the cylindrical portion 2 so that its central aperture 74 is received over the valve stem receiving block 9.

- 6 -

The indicator wheel 40 is supported by the support ring 70 with the lower teeth 46 of the indicator wheel 40 engaging the upper teeth 73 of the support ring 70. As shown, the teeth 46, 73 of the indicator wheel 40 and support ring 70 are sloped relative to one another so as only to allow the indicator ring 40 to rotate relative to the support ring 70 in an anti-clockwise direction as discussed below.

The toothed wheel 41 is supported by the indicator wheel 40 with the downwardly directed teeth 51 of the toothed wheel 41 engaging the upper teeth 47 of the indicator wheel 40. As shown, the teeth 51, 47 of the toothed wheel 41 and indicator wheel 40 are sloped relative to one another so as only to allow the indicator wheel 41 to rotate relative to the toothed wheel 41 in an anti-clockwise direction as discussed below.

The bearing plate 42 is supported by the toothed wheel 41 with the lower teeth 57 of the bearing plate 42 engaging the upwardly directed teeth 52 of the toothed wheel 41. As shown, the teeth 57, 52 of the bearing plate 42 and toothed wheel 41 are sloped relative to one another so as only to allow the toothed wheel 41 to rotate relative to the bearing plate 42 in an anti-clockwise direction, as discussed below. The notches 58 engage the longitudinal ribs 14 of the housing 1 to prevent the bearing plate 42 rotating relative to the housing 1 whilst allowing relative axial movement therebetween.

During assembly, the indicator wheel 40, toothed wheel 41, bearing plate 42 and support ring 70 are inserted before the pressurised dispensing container 20. The valve stem 22 passes through the central apertures 56 and 53 of the bearing plate 42 and toothed wheel 40 before being received in the bore 12 of the valve stem receiving block 9. A leading face



- 7 -

24 of the ferrule 23 bears against the bearing plate 42.

In use, a user operates the pressurised dispensing container 21 by depressing the canister  
5 body 21 axially to move it relative to the cylindrical portion 2 of the housing 1. As a result, the valve stem 22 is inwardly retracted relative to the metering valve such that a dose of product is dispensed from  
10 the valve stem 22 into the bore 12 and duct 11 of the valve stem receiving block 9. The product is then channelled by duct 11 and dispensed as an aerosol through orifice 10 into the outlet duct 4. The aerosol is inhaled by a user inhaling on outlet 5 of the mouthpiece 3.

15 According to the present invention, as the canister body 21 is axially depressed, the leading face 24 of the ferrule 23 bears against and axially displaces the bearing plate 42.

During this axial movement the bearing plate 42  
20 is prevented from rotating because of the engagement of the longitudinal ribs 14 in the notches 58.

The force needed to slide the support ring 70 relative to the cylindrical portion 2 is significantly greater than that needed to actuate the metering  
25 valve. Hence, during a normal operating cycle support ring 70 does not move axially. Consequently, indicator wheel 40 is prevented from moving axially. As a result, axial movement of the bearing plate 42 acts to compress the toothed wheel 41 such that the  
30 downwardly and upwardly directed teeth 51, 52 are brought towards, and into, the plane of the annular disc portion 50. This movement causes the indicator wheel 40 to rotate by an increment.

When the user releases the canister body 21, the  
35 canister body 21 returns to its original position due to the internal spring bias of the metering valve. At the time, the bias of the downwardly and upwardly

- 8 -

directed teeth 51, 52 of the toothed wheel 50 act to push apart the indicator wheel 40 and bearing plate 42, back into their rest positions. The angling of the teeth on the bearing plate 42, toothed wheel 41, indicator wheel 40 and support ring 70 prevent any reverse movement of the indicator wheel 40 during this part of the operating cycle.

Therefore, on each actuation of the pressurised dispensing container 20 the indicator wheel 40 is rotated an increment such that the subsequent indicia 45 is visible through the viewing window 8 in the housing 1.

The dosage counter is 'set' in the housing 1 on the first actuation as follows:

The support ring 70 is assembled in the cylindrical portion 2 of the housing 1 at a point above its normal operating position, i.e., nearer the open end 6 of the housing 1 than shown in Figure 1.

Consequently, the indicator wheel 40, toothed wheel 41 and bearing plate 42 are all also nearer the open end 6 than their normal operating positions. On the first actuation, which may be undertaken by the user or at the point of manufacture or sale, the leading face 24 of the ferrule 23 initially axially moves the bearing plate 42 without moving the support ring 70. Once the toothed wheel 41 has been completely compressed (during which movement the metering valve is actuated), the user, pharmacist or manufacturer applies a higher axial force to the canister body 21 to move both the bearing plate 42 and support ring 70 axially until the retracted valve stem 22 'grounds' against the base of the receiving bore 12 of the valve stem receiving block 9. The support ring 70 is now in its normal operating position and is 'set'. The setting of the support ring 70 takes into account any variations in distance between the leading face 24 of the ferrule 23 and the end of the valve

- 9 -

stem 22. Without this feature, it is possible for variations in pressurised dispensing containers to mean that in certain circumstances, the metering valve may be actuated before the indicator wheel 40 rotates or vice versa.

5

- 10 -

## Claims:

1. Apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising an annular counter member and a driving member, the driving member comprising a planar ring portion and first and second sets of flexible teeth depending from opposite sides of the planar ring portion, the first set of dependant flexible teeth engaging a first series of teeth formed on the annular counter member, wherein on movement of the received dose-dispensing container towards the driving member the first and second sets of dependant flexible teeth are caused to flex towards the plane of the ring portion to thereby incrementally rotate the annular counter member in a first direction relative to the housing.
2. Apparatus as claimed in claim 1 further comprising a support member slidably received in the housing to support the annular counting member and driving member in proper alignment.
3. Apparatus as claimed in claim 2 wherein the support member comprises a series of teeth engagable with a second series of teeth formed on the annular counter member, so as to prevent rotation of the annular counter member in a direction opposed to the first direction.
4. Apparatus as claimed in any preceding claim wherein the dose counter further comprises a bearing member against which a surface of the received dose-dispensing container bears, the bearing member comprising a series of teeth engagable with the second set of dependant flexible teeth of the driving member, such that movement of the bearing member towards the

- 11 -

driving member causes the driving member to rotate relative to the bearing member.

5        5.    Apparatus as claimed in any preceding claim wherein the annular counter member comprises a series of indicia around its periphery.

10       6.    Apparatus as claimed in claim 5 wherein the indicia are visible to a user through a window formed in the housing.

7.    Apparatus as claimed in any preceding claim wherein the driving member is formed from sheet metal.


15       8.    Apparatus as claimed in claim 7 wherein the teeth of the driving member are dependent flanges pressed from the sheet metal.

20       9.    Apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising an annular counter member, a driving member for translating reciprocal motion of the received dose-dispensing container into rotary motion of the annular  
25       counter member, and a support member for supporting the annular counter member and driving member in proper alignment with the received dose-dispensing container, wherein the support is an interference fit in the housing such that a first actuation of the  
30       received dose-dispensing container sets the position of the support relative to the received dose-dispensing container and housing.

35       10.   Apparatus substantially as hereinbefore described with reference to and as shown in the accompanying drawings.


1/2

FIG. 1.



2/2

FIG. 2.



(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
6 September 2002 (06.09.2002)

PCT

(10) International Publication Number  
**WO 02/069252 A3**

(51) International Patent Classification<sup>7</sup>: **G06M 1/04**

27514 (US). **BRACE, Geoff** [GB/US]; 3421 Savan Court, Raleigh, NC 27613 (US).

(21) International Application Number: PCT/GB02/00767

(22) International Filing Date: 22 February 2002 (22.02.2002)

(74) Agents: **ALEXANDER, Thomas, Bruce** et al.; Boulton Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0104556.6 23 February 2001 (23.02.2001) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **BESPAK PLC** [GB/GB]; Bergen Way, North Lynn Industrial Estate, King's Lynn, Norfolk PE30 2JJ (GB).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **OUYANG, Tian-hong** [US/US]; 161 Kingston Drive, Chapel Hill, NC

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,

[Continued on next page]

(54) Title: DOSAGE COUNTING DEVICES



(57) Abstract: Apparatus comprising a housing (1) defining a portion (2) for receiving in use a dose-dispensing container (20), the housing containing a dose counter comprising an annular counter member (40) and a driving member (41), the driving member comprising a planar ring portion (50) and first and second sets of flexible teeth (51, 52) depending from opposite sides of the planar ring portion, the first set of dependant flexible teeth (51) engaging a first series of teeth (47) formed on the annular counter member, wherein on movement of the received dose-dispensing container towards the driving member the first and second sets of dependant flexible teeth are caused to flex towards the plane of the ring portion to thereby incrementally rotate the annular counter member in a first direction relative to the housing.

WO 02/069252 A3





GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**(88) Date of publication of the international search report:**

21 November 2002

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/00767

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G06M1/04

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 480 488 A (ELETTRIO PLASTICA SPA) 15 April 1992 (1992-04-15)	10
Y		9
A	column 1, line 38 -column 2, line 24 column 3, line 30 -column 4, line 53; figures ---	1-5
Y	US 6 155 251 A (HAUSER STEPHEN G) 5 December 2000 (2000-12-05) column 5, line 27 -column 7, line 27; figures ---	9
A	WO 98 56444 A (BONNEY STANLEY GEORGE ;GODFREY JAMES WILLIAM (GB); RAND PAUL KENNE) 17 December 1998 (1998-12-17) page 10, paragraph 2 --- -/--	9



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

22 July 2002

Date of mailing of the international search report

11.09.2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Gélébart, Y

## INTERNATIONAL SEARCH REPORT

ational Application No

PCT/GB 02/00767

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 228 586 A (FUCHS KARL-HEINZ) 20 July 1993 (1993-07-20) ----	
A	WO 95 08484 A (SENETICS INC) 30 March 1995 (1995-03-30) cited in the application -----	

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/GB 02/00767

### Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

### Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

#### Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-8,10

Dose dispenser comprising a dose counter having a drive member comprising a planar ring with flexible teeth depending from opposite sides of the planar ring.

2. Claim : 9

Dose dispenser comprising a dose counter where the counter support member is set into place by the first actuation of the dose dispenser.

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/00767

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0480488	A	15-04-1992	IT 1243820 B AT 113486 T AU 646873 B2 AU 8025891 A BR 9103035 A CA 2046806 A1 DE 69104950 D1 DE 69104950 T2 EP 0480488 A1 ES 2066336 T3 JP 3211894 B2 JP 5228213 A US 5174473 A	28-06-1994 15-11-1994 10-03-1994 16-04-1992 16-06-1992 10-04-1992 08-12-1994 09-03-1995 15-04-1992 01-03-1995 25-09-2001 07-09-1993 29-12-1992
US 6155251	A	05-12-2000	US 5904139 A	18-05-1999
WO 9856444	A	17-12-1998	AT 215389 T AU 741693 B2 AU 8213798 A AU 741218 B2 AU 8213898 A AU 742913 B2 AU 8436498 A BR 9809554 A BR 9809980 A BR 9809983 A CN 1265601 T DE 69804609 D1 EG 21520 A WO 9856444 A1 WO 9856445 A1 WO 9856446 A1 EP 1163922 A2 EP 0988077 A1 EP 0988078 A1 EP 0986412 A1 HR 980304 A1 HU 0003328 A2 JP 2000513632 T JP 2000513633 T JP 2000513634 T NO 996085 A NZ 501379 A PL 337316 A1 TR 9903066 T2 US 6360739 B1 ZA 9804944 A	15-04-2002 06-12-2001 30-12-1998 29-11-2001 30-12-1998 17-01-2002 30-12-1998 20-06-2000 01-08-2000 01-08-2000 06-09-2000 08-05-2002 28-11-2001 17-12-1998 17-12-1998 17-12-1998 19-12-2001 29-03-2000 29-03-2000 22-03-2000 30-04-1999 28-02-2001 17-10-2000 17-10-2000 17-10-2000 09-02-2000 26-04-2002 14-08-2000 21-07-2000 26-03-2002 08-12-1999
US 5228586	A	20-07-1993	AT 137142 T DE 59107710 D1 EP 0472915 A2 ES 2086438 T3 JP 3164229 B2 JP 5124688 A	15-05-1996 30-05-1996 04-03-1992 01-07-1996 08-05-2001 21-05-1993
WO 9508484	A	30-03-1995	US 5421482 A WO 9629278 A1 AU 688794 B2	06-06-1995 26-09-1996 19-03-1998

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/00767

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9508484	A	AU 7732794 A	10-04-1995
		BR 9407608 A	14-01-1997
		CA 2172537 A1	30-03-1995
		CN 1133584 A ,B	16-10-1996
		EP 0720568 A1	10-07-1996
		JP 9502951 T	25-03-1997
		WO 9508484 A1	30-03-1995
		US 5611444 A	18-03-1997
		US 5718355 A	17-02-1998
		US 5799651 A	01-09-1998

---